

4000XLS

Residential
Single / Dual

Swing Gate Operator



For Swing Gates
UP TO 20 ft long
and 1000 lbs per leaf



All Models Listed;
UL325 Compliant



Intertek

Supporters and Proud Members of



- Full-systems capable, “add-on ready,” heavy-duty control board includes adjustable obstruction sensing, gate sequencing and auto close settings (0-120 seconds)
- Easy transmitter programming with the touch of a button
- Includes battery backup, 318 MHz RF radio receiver, entry transmitter, AC transformer and all necessary mounting hardware for a post-mounted installation, 19" (43 cm) total offset)
- Soft start / soft stop
- Low voltage system — no electrician or welding required
- 2-year warranty (single family residential applications only)

Linear
PRO ACCESS®

ELECTRICAL

- 12 Volt DC / 7.0 amp hour, sealed, rechargeable battery (included). Battery charge is maintained by a 120V AC/60 Hz input, 18V AC, 40 VA. output, transformer rectified to 14V DC through control board.
- Powered by a reliable 12 Volt (120 Watt) DC motor, 16:1 planetary gear drive system.
- Charging regulated circuit on control board. "Sleep draw" is 15 mA; "active draw" is 3 to 7 amps.

MECHANICAL

- The control board can be programmed for pull-to-open or push-to-open
- Operating temp -5 F (-21C) to +160 F (71 C)
- Opening time: 18 to 20 seconds
- Range of arm stroke: up to 21" (41 cm)
- Operator length: with arm fully retracted is 46.25" (102 cm), mounting point to mounting point
- Operation, diagnostic and safety alarms
- Inherent obstruction sensing
- Soft start/soft stop for long mechanical life expectancy
- Auto close adjustable 3- to 120-second delay

MODEL	TYPE	VOLTS	Max. Gate Length	Max Gate Weight	Gate Speed
PRO-SW4000 XLS	Single	12 V DC	20'	1000 lbs	18-20 sec
PRO-SW4200 XLS	Dual				

(solar charger optional)

DUAL GATES

- The PRO-SW4200XLS works as a second gate operator when combined with a PRO-SW4000XLS. The PRO-SW4200XLS includes a 50ft power cable.



FEATURES:

- Solar Compatible
- Increased operating speed by 10%
- NEW rev-counter board with reed switch technology
- Reinstated heavy duty hardware for 1000lb-20 ft gates
- IMPROVED front mount and scraper seal design
- Features soft start and stop operation
- Extended Cycle Life — Enhanced motor design makes this opener ideal for today's single family homes or ranches.
- Works on all types of gates: chain link, tube, panel, ornamental, wood and vinyl
- Full systems capable, control board includes an adjustable obstruction sensing, gate sequencing and auto close settings
- U.L. rated for Class I. System certified to be in compliance with U.L. 325, latest revision

CAUTIONS



- Automatic gates not for pedestrians
- Automatic gate operators designed for vehicular traffic only; operators are powerful and can cause serious injury or death; **DIRECT ALL PEDESTRIAN TRAFFIC TO SEPARATE PEDESTRIAN GATE**
- UL325 requires use of contact or non-contact anti-entrapment devices
- ASTM F2200 requires that all exposed rollers are covered